

THE WORLD'S STANDARD FOR SOLAR™
Highest Efficiency | Highest Reliability | Guaranteed Performance

SUNPOWER

Utility Scale Solar PV Project Experience

William Peter

System Engineer, Grid Integration

ERCOT Emerging Technologies Working Group Solar Workshop

April 25th 2011

Safe Harbor Statement

This presentation contains forward-looking statements within the meaning of the Private Securities Litigation Reform Act of 1995. Forward-looking statements are statements that do not represent historical facts and may be based on underlying assumptions. SunPower uses words and phrases such as "expects," "believes," "plans," "anticipates," "continue," "growing," "will," to identify forward-looking statements in this presentation, including forward-looking statements regarding: (a) plans and expectations regarding the company's cost reduction roadmap, (b) cell manufacturing ramp plan, (c) financial forecasts, (d) future government award funding, (e) future solar and traditional electricity rates, and (f) trends and growth in the solar industry. Such forward-looking statements are based on information available to the company as of the date of this release and involve a number of risks and uncertainties, some beyond the company's control, that could cause actual results to differ materially from those anticipated by these forward-looking statements, including risks and uncertainties such as: (i) the company's ability to obtain and maintain an adequate supply of raw materials and components, as well as the price it pays for such; (ii) general business and economic conditions, including seasonality of the industry; (iii) growth trends in the solar power industry; (iv) the continuation of governmental and related economic incentives promoting the use of solar power; (v) the improved availability of third-party financing arrangements for the company's customers; (vi) construction difficulties or potential delays, including permitting and transmission access and upgrades; (vii) the company's ability to ramp new production lines and realize expected manufacturing efficiencies; (viii) manufacturing difficulties that could arise; (ix) the success of the company's ongoing research and development efforts to compete with other companies and competing technologies; and (x) other risks described in the company's Annual Report on Form 10-K for the year ended January 3, 2010, and other filings with the Securities and Exchange Commission. These forward-looking statements should not be relied upon as representing the company's views as of any subsequent date, and the company is under no obligation to, and expressly disclaims any responsibility to, update or alter its forward-looking statements, whether as a result of new information, future events or otherwise.

© 2011 SunPower Corporation



Outline

- Utility Scale Solar PV
 - Introduction to SunPower
 - SunPower Project Examples
 - OASIS: Tracking Solar PV Power Plant Blocks
- Grid Integration of Solar PV
 - Voltage Support
 - Fault Ride Through
 - Active Power Management
 - Frequency Support
 - System Impact Studies

© 2011 SunPower Corporation

SunPower 2011 – The World’s Standard for Solar

- 2010: Revenue \$2.15-\$2.25B
- 5,500+ Employees
- 550+ MW 2010 production
- >1.5 GW solar PV deployed
- 5 GW power plant pipeline
- World-leading solar conversion efficiency
- Diversified portfolio: roofs to power plants
- 1,500 dealer partners, #1 R&C USA



Residential



Commercial




Power Plants




SunPower To Open Operations Center in Austin, TX

- SunPower is expanding into Texas with a new operations center in Austin
- SunPower will create 450 jobs in the region by 2015, beginning with 115 jobs created in 2011
- The new Austin facility will house operations including marketing, legal, and finance functions



© 2011 SunPower Corporation

Over 250 MW of power plants installed in Europe



Serpa, PORTUGAL
11 MW



Isla Mayor, SPAIN
8 MW



Olivenza, SPAIN
18 MW



Jumilla, SPAIN
23 MW



Montalto, ITALY
72 MW



Muehlhausen, GERMANY, 6 MW

SunPower Utility Solar PV Power Plants

- Examples of Project Experience



YEAR	MARKET	MW	NAME
2004	Germany	10	Solar Bavaria
2006	Portugal	11	Serpa
2007	U.S. - Nevada	14	Nellis Air Force Base
2008	Spain	18	Olivenza
2009	U.S. - Florida	35	DeSoto (FPL)
2010	Italy	72	Montalto di Castro
2010	U.S. - Colorado	19	Greater Sandhill (Xcel)
2011	U.S.- California	250	CVSR (PG&E)

© 2011 SunPower Corporation



Montalto 72 MW
Lazio, Italy

SUNPOWER™




Nellis AFB 14 MW: NV energy
Las Vegas, NV, U.S.

SUNPOWER™



Greater Sandhill 19 MW: Xcel
Alamosa County, Colorado, U.S.


California Valley Solar Ranch (CVSR)



- 250 MW PPA with PG&E
- Target Schedule
 - Q3/Q4 2011 – Start of Construction
 - Q4 2011/Q1 2012 – Phase I Complete/First 25MW on-line
 - Q4/2013 – Project Completion
- Permit recently approved by San Luis Obispo county supervisors 5-0

© 2011 SunPower Corporation

SunPower Oasis Power Plant



The SunPower Oasis power plant is a modular utility solar platform consisting of configurable 1.5 MW PV power blocks coupled with a sophisticated plant operating system

The SunPower Oasis Tracker & 425 W Panel



SunPower T0 Tracker

Most installed solar tracker in the world
– 400MW over 10 years

Increases capacity factor by up to 25%

Simple control system = lowest O&M of
any PV power plant fixed or tracking


SunPower 425W panel has today's
highest efficiency



Jeonju, Korea
2 MW

© 2011 SunPower Corporation

Oasis Power Block Enhances Production



© 2011 SunPower Corporation



Outline

- Utility Scale Solar PV
 - Introduction to SunPower
 - SunPower Project Examples
 - OASIS: Tracking Solar PV Power Plant Blocks
- Grid Integration of Solar PV
 - Voltage Support
 - Fault Ride Through
 - Active Power Management
 - Frequency Support
 - System Impact Studies

© 2011 SunPower Corporation

Progress in Solar PV Integration

- Solar PV's initial application was residential and commercial
 - Standards (UL1741, IEEE 1547) intended for distribution networks
 - Inverters for use on distribution networks initially designed without LVRT, voltage control, etc. to meet these requirements
- SunPower Utility Scale PV plants have the technical capabilities to provide features similar to modern wind plants:
 - Ride Through (Voltage and Frequency)
 - Over Frequency Droop Response
 - Real Power Curtailment
 - Reactive Power Support
- Grid integration products in the market are evolving

© 2011 SunPower Corporation

OASIS Grid Integration Options

- Reactive Power
 - +/- 0.95 PF at POI
 - Voltage, Power Factor, or Reactive Power Control

- Fault Ride-Through
 - Configurable Voltage and Frequency Ride through Windows

- Over Frequency Droop Response

- Active Power Curtailment from 0 to 100%

STATUS/ALARMS

Inverter State	Operation
DSP State	Run
AC CTR State	Closed
CU State	Operation
React Pwr Status	OK
Derate State	Normal
Error Code	0
Error Description	

ANALOGS

DC Power	27.9 kW
DC Current	66.5 A
DC Volts	419.2 V
AC Average Power	24.7 kW
AC Apparent Power	24.7 kVA
AC Reactive Power	-1.3 kVAr
Reactive Power SP	1.0
AC Average Current	71.8 A
Phase 1 Volts	197.7 V
Phase 2 Volts	199.3 V
Phase 3 Volts	199.1 V
Total AC Power	214694.8 kWh
Daily AC Power	3155.0 kWh
Grid Frequency	60.0 Hz
Power Factor	0.0
Core 1 Temp	59.8 °C
Core 2 Temp	0.0 °C
Cab 1 Temp	27.5 °C
Cab 2 Temp	40.0 °C
Xfer Temp	0.0 °C
Operating Time	763.1 H

TRANSDUCERS

DC Current	0.0 A
Inverter Leakage	0.0 mA
DC Voltage	0.0 V

FANS


Cabinet 1 Fan	
Speed	21.0
Operating Time	0.0
Cabinet 2 Fan	
Speed	20.0
Operating Time	0.0
Transformer Fan 1	
Speed	0.0
Operating Time	0.0
Transformer Fan 2	
Speed	0.0
Operating Time	0.0
Core (IGBT) Fan 1	
Speed	0.0
Operating Time	0.0
Core (IGBT) Fan 2	
Speed	0.0
Operating Time	0.0

CONTACTORS

DC Cycle Count	101
AC Cycle Count	2297


© 2011 SunPower Corporation

Reactive Power Requirements



© 2011 SunPower Corporation

Reactive Power as Function of Voltage at POI



© 2011 SunPower Corporation

Example Reactive Power Testing Procedures


Test	Condition	Test	Requirement
Maintain voltage setpoint	P = 25% to >92.5% of Available Capacity	Set voltage setpoint to 1.02 pu	Voltage held within +/- 1%, subject to p.f. limits and Available Capacity. New voltage setpoint(s) may be selected.
Compensate for changing transmission conditions	Q = ~0 MVAR output after LTC is adjusted several steps	Set voltage setpoint as necessary	Q <=0 MVAR at POI
Lead/Lag 0.95 limits	P = 25%, 50%, 75% and >92.5% of Available Capacity, limited to 9.4 MVAR at POI.	Set voltage to demonstrate 0.95 p.f. Lead	Meter shop test equipment indicates 0.95 or less
		Set voltage to demonstrate 0.95 p.f. Lag	Meter shop test equipment indicates 0.95 or less
Raise/lower setpoint	P > 50% of Available Capacity	Series selected at time of test (ex: Raise/Lower voltage 0.005pu)	Voltage at POI is consistent with change in setpoint, subject to p.f. limits and within the ability of the plant to influence the voltage

- Available Capacity = Total plant power output correcting for environmental variables (e.g. irradiance, temperature).

© 2011 SunPower Corporation


Example of Test Demonstration

- Successful test of reactive power tests for SunPower Utility Scale Solar PV Plant
- Demonstrated at range of Power outputs during the morning
- Reaches Full Reactive Power Requirements (± 0.95 pf)



© 2011 SunPower Corporation

Voltage Control



SunPower PV Plant operational in North America with automated voltage control on the transmission system

© 2011 SunPower Corporation

Summary of Reactive Power Requirements

- SunPower Utility Scale PV Plants have demonstrated ability to provide reactive power support and help maintain voltage
- Shared goal of grid reliability and stability
 - Requirements that are designed to promote grid stability and reliability while avoiding market barriers
 - Utility Testing and Operational Requirements

Regulatory Ride Through Requirements


- Rules on Ride through still evolving in U.S. and elsewhere
 - OASIS has configurable Voltage and Frequency Ride though Windows
 - Ex: FERC Order 661-A, NERC PRC-024 (Draft), WECC ONF, MV BDEW
- Example of LVRT Requirement: Ride through three phase faults on transmission grid with normal clearing times (4-9 cycles)

WECC Off-Nominal Frequency (ONF) Tolerance		
Under-frequency Limit	Over-frequency Limit	WECC Minimum Time
> 59.4 Hz	60 Hz to < 60.6 Hz	N/A (continuous operation)
≤ 59.4 Hz	≥60.6 Hz	3 minutes
≤ 58.4 Hz	≥61.6 Hz	30 seconds
≤57.8 Hz		7.5 seconds
≤57.3 Hz		45 cycles
≤57 Hz	>61.7 Hz	Instantaneous trip

© 2011 SunPower Corporation

Ride Through


- Example of operational SunPower Solar PV Plant riding through a disturbance
- Voltage and Frequency Ride Through
- Plant remains online and continues providing power as the grid recovers



See: "METHODS OF INTEGRATING A HIGH PENETRATION PHOTOVOLTAIC POWER PLANT INTO A MICRO GRID", Lars Johnson, 35th IEEE PVSC, Honolulu, Hawaii, June 2010.


Lanai (Hawaii) 1.2 MW Project

- Lanai peak net load: 4.7 MW
- Operational since: December, 2008



© 2011 SunPower Corporation

Example of Active Power Curtailment




See: "METHODS OF INTEGRATING A HIGH PENETRATION PHOTOVOLTAIC POWER PLANT INTO A MICRO GRID", Johnson R, Johnson L, Nelson L, Lenox C, Stein J.

© 2011 SunPower Corporation

Over Frequency Droop

- OASIS has the option of a configurable droop response
- Example: Project currently in late stage development
 - Project expected to start construction this year
 - Specific voltage and frequency issues for local grid
 - Utility interested in option of Over-Frequency Droop Response
- Not aware of any requirements for over frequency droop for a currently operational Solar PV Plant in U.S.

Example Simulation: Over Frequency Droop



© 2011 SunPower Corporation

System Impact Studies for Solar PV Plants

- Assess impacts on system reliability and stability
- California ISO Cluster Process
 - Over 16,000 MWs of Solar PV in Interconnection Queue
 - Power flow, dynamic stability, and short circuit studies
- SunPower has provided Plant Level Equivalent Models for System Impact Studies
 - Proprietary positive sequence models (PSSE/PSLF) exist today for Solar PV inverters
 - WECC Renewable Energy Modeling Task Force (REMTF)

© 2011 SunPower Corporation

Summary of Grid Support

- SunPower Utility Scale PV plants have demonstrated ability to provide:
 - Voltage Support
 - Ride through disturbances on the grid
 - Active power management
 - Over frequency droop response
- Models of Solar PV Plants available for System Impact Studies
- Shared goal of requirements that promote grid reliability and stability while avoiding market barriers

Summary

- Thank you for the opportunity to present our experiences!
- SunPower has over 1.5 GW of solar PV deployed worldwide
- The OASIS Power Plant with grid integration options:
 - Ride Through (Voltage and Frequency)
 - Over Frequency Droop Response
 - Real Power Curtailment
 - Reactive Power Support
- A thank you for all the helpful support to: Kari Smith, Alan Comnes, Carl Lenox, Chris Barker, Robert Johnson, Lars Johnson, and many others from the SunPower team
- Contact Information:
 - William Peter: william.peter@sunpowercorp.com
 - John Pitts: john.pitts@sunpowercorp.com



© 2011 SunPower Corporation

www.sunpowercorp.com

